

Hakusan (Thailand) Co., Ltd.

Company profile & Products & Solution

2024/7/1

1



HAKUSAN THAILAND

> Location : Lamlukka, Pathumthani

➤ Since Jan. 2016

> Employee: 10

> Main products:

Chip conveyor

Coolant tank

• Filter equipment

➤ Total production: 400set (~May 2020)

> Equipment

Laser cut machine x 1

Press brake machine x 1

• Welding machine x 4

• Roll bender x 1





2024/7/1

2



GROUP PROFILE

HAKUSANKIKO



● TOTAL PRODUCTION 100,000SET (~2019)

• EMPLOYEE: 114

• LOCATION : Ishikawa, Japan



HAKUSAN MACHINERY(Wuxi)



● TOTAL PRODUCTION 10,000SET (~2019)

• EMPLOYEE: 120

• LOCATION : Shanghai, China



HAKUSAN KOREA 🥯

MAIN PRODUCTS : DELIVERY BOX

LOCATION :Seoul, Korea



Main user & Customer

Machine maker

- Fanuc
- Brother
- Makino
- Okuma
- Mori seiki
- OKK
- Enshu
- Horkos
- Itekt
- Yasuda
- Mazak
- Mitsui seiki
- Sugino 2024/7/1

- Takamaz
- Tsugami
- Takisawa
- Citizen Miyano
- Murata
- Fujikikai
- Star
- Hasegawa
- Amada

- Komatsu NTC
- Howa
- Sakurai
- Nachi
- Kanzaki
- Nishida
- Miroku
- Fuji-horning
- Yasunaga
- First-giken

End user (Hopper, Centerized etc)

- Mazda
- Denso
- Suzuki
- Ahresty
- Art
- Aisin AW
- Stanley
- Isuzu

Machining

- Special, Grinding, Gundrill, etc

Main products

AHAKUSAN

- Chip conveyor
- >Floor
- **>**Scraper
- **≻**Coil



Coolant system


- ➤ Drum filter scraper conveyor
- ➤ Coolant tank



AHAKU/AN

Purpose of chip conveyor

✓Transfer chips from inside machine to chip cart automatically.



- Lose machine operating time
- (2) Hard, Dangerous, Dirty work

- Good for worker

AHAKU/AN

Chip conveyor lineup Catalog P.3,4









Floor conveyor

Scraper conveyor

iron







Magnet <u>scraper</u> conveyor



Drum filter scraper conveyor

tangled







Coil conveyor



Floor conveyor

- For long chips (over 50mm)
- Conveyor width 250-600mm
- Angle0°,30°,45°,60°,75°
- Conveyor length under 10m
- Two type speed0.9m/min or 1.7m/min
- Safety device protect relay or torque limit
- Options:
 - Control box
 - Coolant returner
 - Enhanced hinge
 - Dimple hinge



2024/7/1

Catalog P.5,6

LATHE MACHINE × FLOOR CONVEYOR A HAKUSAN











Scraper conveyor


Catalog P.7,8,9

- For short chips (under 50mm)
- Conveyor width 250-600mm
- Angle 0° ,30° ,45° ,60° ,75°
- Conveyor length under 15m
- Safety device protect relay or torque limit
- Options:
 - Control box
 - Coolant returner
 - Magnet scraper
 - Wedge wire






Normal scraper conveyor



solution1

Magnet scraper conveyor






12

solution2


AHAKUSAN

Wedge wire filter scraper conveyor





ROBODRILL × SCRAPER CONVEYOR





MACHINING CENTER

× MAGNET WEDGE WIRE SCRAPER CONVEYOR





AHAKU/AN

Coil conveyor

- For tangled chips
- Conveyor width 350-600mm
- Conveyor length under 3m
- Options:
 - Control box
 - Enhanced coil




LATHE MACHINE × COIL CONVEYOR











202477/1

Ι,

Purpose of Coolant system

- 1. Supply coolant to machine.
 - Coolant clean up inside machine.
 - Coolant cool down machine and tooling.
 - Lubrication
- 2. Filtering chips and sludge by using several filter.

















COOLANT SYSTEM LAYOUT (Example)




Pump for back wash

1st Tank





COOLANT FILTERING FLOW(Example)



Drum filter scraper conveyor



- For short aluminum chips (under 50mm)
- Filter mesh #80 or 200
- Automatic filter cleaning
- Conveyor width 400-800mm
- Angle 60°,75°
- Safety device protect relay or torque limit
- Options:
 - Control box
 - Coolant returner
 - Pump, level gage, oil skimmer etc.
 - Magnet
 - Notch wire drum





MACHINING CENTER × DRUM FILTER SCRAPER






Cyclone filter

1st tank

 $50\sim100\,\mu\,{\rm m}$

Catalog P.16





2nd tank

 $20 \,\mu$ m

Flow rate : 22-310L/min Accuracy : 20μ m 90%

Merit

- Maintenance free
- No consumable goods

Demerit

- Coolant temperature up
- Oil coolant can't use

AHAKUSAN

Magnet separator Catalog P.15



Flow rate : 40-240L/min Accuracy : $7-10 \mu$ m 99%


Model MHF, MHK

• Just for magnetic material

• MHF is normal magnet

MHK is high performance magnet

Oil coolant can use



Oil skimmer

For collect floating oil

HOS-25


- · Belt width 25mm
- Length 165, 250, 350mm
- Capacity 10L/h (max)

HOS-75

- Belt width 75mm
- Length 300,600,900mm
- Capacity 50L/h (max)








Other chip conveyor & coolant tank



Twin chip conveyor(PDM II) Catalog P.13

For Long and short chips →Floor + drum filter scraper conveyor



Floor conveyor



Drum filter scraper conveyor

Other chip conveyor & coolant tank



Concentrated conveyor

Catalog P.17





<u>sample</u>



Other chip conveyor & coolant tank


Pump back system

Catalog P.18

 Coolant and chips flow to main coolant tank from <u>funnel tank</u> attached by each machine.

Merit <u>sample</u>

- ✓ Small machine space
- ✓ Free layout
- ✓ Easy coolant concentration control





28

Other products



Suction tower cleaner


- ✓ Portable
- ✓ Air supply only
- ✓ Coolant lifespan up

Specification

■ Capture max: 15L

■ Flow rate: 40-50L/min

■ Accuracy: 10μ m



Other products



FILSTER all-in-one unit

- ✓ Portable
- ✓ Easy to install
- ✓ Coolant lifespan up
- ✓ No consumables

FILSTER Specification

■ Flow rate: 15-60L/min

 \blacksquare Accuracy: $10 \,\mu$ m

■ Power supply :200V/50Hz

TEST unit

■ Flow rate: 15-20L/min

■ Accuracy : 10μ m

■ Power supply: 200V50Hz



Other products CHIP CART









Other products



Lifter & Hopper Chip collection & disposal system

Catalog P.17







Repair & Restore service

Before





After



- ✓ Many stock parts
- ✓ Sheet metal parts and machine parts are shorts time delivery.
- ✓ Re-paint



Delivery box "AZUKARI-KUN"





- Touch monitor
- QR code



TV CM